

## Tabella °C / Ohms per Pt100 RTD's

|     |       |    |        |    |        |     |        |     |        |     |        |     |        |
|-----|-------|----|--------|----|--------|-----|--------|-----|--------|-----|--------|-----|--------|
| -50 | 80.25 | 0  | 100.00 | 50 | 119.40 | 100 | 138.50 | 150 | 157.32 | 200 | 175.84 | 300 | 212.03 |
| -45 | 82.23 | 5  | 101.95 | 55 | 121.32 | 105 | 140.39 | 155 | 159.19 | 210 | 179.51 | 350 | 229.69 |
| -40 | 84.21 | 10 | 103.90 | 60 | 123.24 | 110 | 142.28 | 160 | 161.05 | 220 | 183.17 | 400 | 247.06 |
| -35 | 86.19 | 15 | 105.85 | 65 | 125.16 | 115 | 144.17 | 165 | 162.91 | 230 | 186.82 | 450 | 264.14 |
| -30 | 88.17 | 20 | 107.79 | 70 | 127.07 | 120 | 146.06 | 170 | 164.76 | 240 | 190.46 | 500 | 280.93 |
| -25 | 90.15 | 25 | 109.73 | 75 | 128.98 | 125 | 147.94 | 175 | 166.62 | 250 | 194.08 | 550 | 297.43 |
| -20 | 92.13 | 30 | 111.67 | 80 | 130.89 | 130 | 149.82 | 180 | 168.47 | 260 | 197.70 | 600 | 313.65 |
| -15 | 94.10 | 35 | 113.61 | 85 | 132.80 | 135 | 151.70 | 185 | 170.32 | 270 | 201.30 | 650 | 329.57 |
| -10 | 96.07 | 40 | 115.54 | 90 | 134.70 | 140 | 153.57 | 190 | 172.16 | 280 | 204.88 | 700 | 345.21 |
| -5  | 98.04 | 45 | 117.47 | 95 | 136.60 | 145 | 155.45 | 195 | 174.00 | 290 | 208.46 | 800 | 375.61 |